Loaders
Utility Track

Easy to operate

The versatile stand-on utility track loaders are designed for operator comfort, ease of operation and offers a low maintenance design to reduce maintenance cost.

Perfect for a variety of projects

These utility track loaders offer wide tracks and overall narrow machine widths allowing them to fit through doorways, gates and other tight spaces, making them ideal for landscape and residential projects.

Performance

- Class-leading travel speed to help get more done, faster
- Industry attachment interface for use with compatible attachments and increased applications

Efficiency

- Optimized radial path provides vertical lift performance for dumping in trucks or reaching into truck beds
- Auxiliary hydraulic flow is available to power a wide variety of money saving attachments

Maintenance

- Durable undercarriage reduces maintenance costs and total cost of ownership through innovative design and quick maintenance
- Sealed idlers and triple flanged rollers provide added surface area and engagement to reduce wear and de-tracking

Performance Data

	Unit	SM60	SM100	SM120
Max. operating power at operating speed	**hp rpm**	26.5 @ 2,600	24.7 @ 2,600	24.7 @ 2,600
Engine type		Kohler ECH749, air-cooled, 2-cylinder, gasoline engine.	Yanmar 3TNV80FT, liquid-cooled, 4-cycle, 3-cylinder, turbocharged diesel engine.	Yanmar 3TNV80FT, liquid-cooled, 4-cycle, 3-cylinder, turbocharged diesel engine.
Rated Operating Capacity (ROC)	**lbs**	600 @ 35%	1,000 @ 35%	1,226 @ 35%
Tipping load	**lbs**	1,720	2,855	3,504
Fuel tank capacity	**gal**	14	14.1	14.1
Hydraulic tank capacity	**gal**	1.3	1.3	1.3
Max travel speed, single / two-speed	**mph**	3.9	5.2	5.2
Aux. hydraulic flow rate - low / high	**gpm**	12.4	13	13
Aux. hydraulic pressure	**psi**	3,045	3,045	3,045
Overall length w/std. bucket / w/o bucket	**in**	98.5 / 75.3	108 / 84.8	108.3 / 84.7
Overall width	**in**	35.5	35.5	41
Overall height	**in**	54.8	58.2	58.2
Track width	**in**	7	9	11
Hinge pin height	**in**	75.6	85.6	85.6
Ground clearance	**in**	6.8	7.8	7.8
Dump angle at max. height	**deg**	37.3	38.2	38.2
Reach at max. height	**in**	27	23.8	23.6
Breakout force - bucket	**lbf**	2,498	3,110	3,235
Angle of departure	**deg**	23.7	25.6	25.6
Operating weight	**lbs**	2,760	3,300	3,754

www.wackerneuson.com

©Wacker Neuson 2024. Right to make technical amendments reserved.

Facebook Instagram Youtube LinkedIn

0986278
2 / 2024